


High Efficient Rectifier diodes



Features

- Based on silicon planar process, low V_f
- High surge forward current capability
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package:** TOLL
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked

■Maximum Ratings ($T_j=25^{\circ}\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR4580E
Device marking code			MUR4580E
Repetitive Peak Reverse Voltage	V_{RRM}	V	800
Average Rectified Output Current @60Hz half sine-wave, R-load, T_c (FIG.1)	I_o	A	45
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, $T_j=25^{\circ}\text{C}$	I_{FSM}	A	600
Current Squared Time @1ms≤t≤8.3ms $T_j=25^{\circ}\text{C}$	I^2t	A^2s	1494
Storage Temperature	T_{stg}	$^{\circ}\text{C}$	-55 ~ +150
Junction Temperature	T_j	$^{\circ}\text{C}$	-55 ~ +150
Typical Junction capacitance @4V,1MHz	C_j	pF	339



MUR4580E

■Electrical Characteristics (T_j=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Instantaneous forward voltage drop per diode	V _{FM}	V	I _{FM} =45.0A T _j =25°C	-	0.91	0.96
			I _{FM} =45.0A T _j =125°C		0.81	0.86
DC reverse current at rated DC blocking voltage per diode	I _{RRM1}	μA	V _{RM} =V _{RRM} T _j =25°C	-	-	5.0
	I _{RRM2}		V _{RM} =V _{RRM} T _j =125°C	-	-	200
Reverse Recovery Time	T _{rr}	ns	I _F =0.5A I _{RM} =1A I _{RR} =0.25A T _j =25°C	-	850	1000
			T _j =25°C	-	465	-
			T _j =125°C	-	547	-
Peak recovery current	I _{RRM}	A	T _j =25°C	-	43.4	-
			T _j =125°C	-	49.1	-
Reverse recovery charge	Q _{rr}	μC	T _j =25°C	-	13.4	-
			T _j =125°C	-	17.9	-

■Thermal Characteristics (T_j=25°C Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	MUR4580E
Thermal Resistance	Between junction and case	R _{θJ-C}	°C/W	0.5
	Between junction and Air	R _{θJ-A}	°C/W	35

■Ordering Information (Example)

PREFERRED P/N	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR4580E	Approximate 0.8	2000	4000	20000	Reel



■ Characteristics (Typical)

FIG1: I_o - T_c Curve




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage




FIG4: Typical Reverse Characteristics






FIG.5 Diagram of circuit and Testing wave form of reverse recovery time



Outline Dimensions



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	2.2	2.3	2.4
A1	1.7	1.8	1.9
b	0.7	0.8	0.9
b1	9.7	9.8	9.9
b2	1.1	1.2	1.3
c	0.4	0.5	0.6
D	10.28	10.38	10.48
D1	10.98	11.08	11.18
D2	3.2	3.3	3.4
D3	4.45	4.55	4.65
E	9.8	9.9	10
E1	8	8.1	8.2
e	1.2 BSC		
H	11.58	11.68	11.78
H1	6.95 BSC		
i	0.1 REF		
j	0.46 REF		
L	1.5	1.6	1.7
L1	0.6	0.7	0.8
L2	0.5	0.6	0.7
L3	0.3	0.4	0.5
Q	8 REF		
R	3.0	3.1	3.2

Note:

1. Controlling dimension: in millimeters.
2. General tolerance: ± 0.03 mm.
3. The pad layout is for reference purposes only.

UNIT: mm



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.